

Refrigeration for Pharmacies - Pharma Refrigerator +2 / +8°C - EVO Line Model MPR-460

Model:	
Name :	
Project Name :	
Project Area :	
Project Item :	



Refrigeration for Pharmacies - Pharma Refrigerator +2 / +8°C - EVO Line

Model: MPR-460

Reference	19108377
Dimensions (mm)	626 x 740 x 1865
Gross internal volume (L)	460
Number of shelves	5
Termperature	+2/+8°C

General features

Pharmacy Refrigerators Effimed - EVO Line

Effimed, with 35 years of Efficold experience, leads the laboratory refrigerators and freezers sector, offering quality, reliability, and precision.

All our products are developed and tested according to the most demanding international standards: We measure temperature stability according to DIN 13277 standard using 9 sensors inside the chambers.

The EVO line additionally adds a 12-hour battery to maintain alarms, probes, and temperature recording + a power failure alarm.

Design and Construction

- White steel body, both exterior and interior, resistant and easy to clean.
- Adjustable metal shelves with plastic finish and flexibility for different heights.
- Double glass door with low emissions, security lock, and option to change opening direction.
- Flexible installation thanks to rear wheels, height adjusters, and 15 mm hole for external probes.

Technical Specifications

- Stable temperature range between 2 and 8 °C, verified at 9 points according to DIN 13277 standard.
- Interior LED lighting, automatically activated when the door is opened or via manual switch.
- Dynamic cooling with automatic defrost and hidden condensate evaporation system.

Control and Safety

- Intelligent controller with memory to record maximum and minimum temperatures.
- Visual and audible alarms to alert about out-of-range temperatures, open door, or sensor errors.

 Safety thermostat to prevent drops below 2 °C.

 Technological compatibility with RS 485 and potential-
- free contact for remote monitoring.

Efficiency and Sustainability

- Climate class 4, designed to operate in environments up to 32 °C and 60% humidity.
- Clean Hydrocarbon gases, environmentally friendly.

Options

- Voltages: 110/60 Hz and 220/60 Hz.
- Blind door.







Packaging dimensions:
Gross length (Front view): 666 MM
Gross width (Depth): 780 MM
Gross height 2010 MM
Gross / packaged weight: 93 KG

MEASURES AND WEIGHT	
Net High (mm):	1865
Net Depth (mm):	740
Net Width (mm):	626
Gross weight / packaged (kg):	93
Gross height / packaged (mm):	2010
Gross width / packaged (mm):	780
Gross length / packaged (mm):	666
PRODUCT SPECIFICATIONS MEDICAL	000
Wheels:	Yes
Lock:	Yes
Inner material:	Painted sheet
Number of bodies:	1
Glass door:	Yes
Plug type:	European (Type F)
Phases:	1N
Noise level (dB):	0
Number of drawers:	5
Market Scope:	European
Gross internal volume (L):	460
Shelf material:	Plastic-coated Steel
Reversible door L/R:	Yes
Ozone:	No
Number of shelves:	5
Inner height (mm):	1636
Inner width (mm):	547
Inner depth (mm):	501
External material:	Pre-lacquered sheet metal
Insulation thickness:	60
External probe access (number):	1
Sliding pull-out drawers:	No
COLD TECHNICAL SPECIFICATIONS MEDIC	CAL
Gas type:	R-600a
Refrigeration power (KW):	0.292
Condensation system:	Static
Lamp (W):	8
Termperature:	+2/+8°C
SubFamilia:	CO2
Team:	Airtight
Cooling gas load (KG):	0,082
GWP:	3
	Uno
Numero compartimientos:	
Type of cooling: Number of compressors:	Ventilated 1
ELECTRICITY TECHNICAL SPECIFIC. MEDIC	·
	50Hz
Electric frequency:	
Electric power (KW):	0,230
Voltage:	230V
Amperage (A):	1,3A

CONTROLLER SECURITY MEDICAL		
CONTROLLER SECURITY MEDICAL		
High-low temperature alarm:	Yes	
Power failure alarm:	Yes	
Low battery alarm:	Yes	
Probe failure alarm:	Yes	
Door open alarm:	Yes	
USB port:	No	
RS485:	Yes	
Max and min temperature memory:	Yes	
Power free contact:	Yes	
Safety thermostat:	Yes	
Data Logger:	No	
WIFI connection:	No	
Controller with password:	Yes	
ENERGY EFFICIENCY LABEL EURO MEDICAL		
Climate class:	4	
Clasif. Energy efficiency:	F	
Power consumption 24h (KWH):	1,570	





Related families



Perfect Line

