

Chest freezer ULT C400



- Low cost of ownership
- Limited maintenance and on-site service
- Easily installable & movable
- Eco-friendly, HCFC-free Nature R refrigerant
- Efficient cyclopentane insulation
- ISO 9001, 14001 & 45001 Certified

Specifications	
Technical	
Gross volume	383 litres
Net volume	368 litres
Temp. range	-60°C to -86°C
Temp. probes	1/PT 1000
Compressor	Secop
Refrigerant	Nature R
Noise level	55 dB
Power consumption 24/h	9 kWh
Power consumption	3.285 kWh / year
Voltage	220-240V
Frequency	50 Hz
Features	
Audible & visual alarm	YES
Castors	4
Integrated lock	YES
Inner lids	4
Defrost	Manual
Battery Backup	48h
USB	NO
Data connection	NO
Digital controller with display	XR30CX
Data logging	NO
High/Low temperature alarm	YES
Porthole for external probe & CO2 backup	Ø 12 mm
Contact for remote alarm	YES
Material	
Inner	Precoated white steel
Outer	Galvanized pre-coated steel
Dimensions	
Height (w. castors)	885 mm
Width	1562 mm
Depth (incl. condenser)	630 mm
Depth (incl. condenser & handle)	680 mm
Net weight	80 kg
Internal dimensions	
Height	635/385 mm
Width	1392/1190 mm
Depth	440 mm
Insulation	80 mm
Insulation type	PUR
Internal humidity	<5 %

ULT C400





Product no. N113004

Storage capacity				
Box height	No. of boxes	No. of racks	Total no. of boxes	Product no.
50 mm	6	3	18	N311200
	11	24	264	N311220
			= 282	
75 mm	4	3	12	N311300
	8	24	192	N311320
			= 204	
100 mm	3	3	9	N311400
	5	24	120	N311420
			= 129	