

SCANSPEED 406

TECHNICAL DATA



HIGHLIGHTS

- Compact & robust small centrifuge, which is ideal for routine low-speed centrifugation.
- Commonly used in the fractionation of blood samples & precipitation of biological samples.
- Automatic lid release and vivid end alarm for easy retrieval of samples.
- Supplied with an angle rotor including 6 aluminium sleeves for 15 mL tubes.

For more information please visit
www.labogene.com

Details

Product family	ScanSpeed
Model:	406
Part number	7607514101
Product type	Clinical low-speed centrifuge
Compliance with	EN 61010-1, EN 61010-2-020, EN 61000-6-1, EN 11201
e-catalogue classification (UNSPSC code)	40161701 Centrifuges

Technical specifications

Unit

Typical application		Routine separation of blood, urine or cells.
Max. RPM/RCF	RPM/x g	4.000/2.075
Max capacity		6 x 15 mL
Time control		Time < 100 min or continuous
RPM/RCF conversion		Yes
Noise level	dB(A)	≤52
ACC/DEC	sec	≤20 / ≤20
Program memory		10
Parameters on display window		RPM(RCF) & min:sec
Imbalance cutout		Yes
Safety lid lock		Yes
Lid drop protection		Yes
Automatic lid release at completion		Yes
Power supply	V/Hz	220/50-60
Power requirements	VA	140
Dimensions (WxDxH)	mm	296x412x206
Weight without rotor	kg	17,5

LaboGene A/S
Bjarkesvej 5
DK-3450 Allerød

Tel (+45) 3940 2566
Fax (+45) 3995 2566
Mail info@labogene.com
Web www.labogene.com

