

Laboratory cold storage - Freezing -25°C - Perfect Line **Model LF-600**

Model:
Name:
Project Name:

Project Area:
Project Item:



Laboratory cold storage - Freezing -25°C - Perfect Line

Model: LF-600

Reference	19108362
Dimensions (mm)	695 x 860 x 2037
Gross internal volume (L)	545
Number of shelves	5
Termperature	-26 -10 °C

General features

Effimed Laboratory Freezers - Perfect Line

Effimed laboratory freezers are designed to offer **precision**, **safety, and efficiency** in the storage of sensitive products. They comply with the most demanding international standards, standing out for their robust construction, advanced functionalities, and customizable options.

Design and Construction

- White exterior and stainless steel interior, durable and easy to clean.
- Adjustable shelves with metal grid and plastic finish.
- Blind door with lock, with the option to change the opening direction.
- Wheels with brake for easy mobility.
- 80 mm thermal insulation, ensuring temperature stability.
- 15 mm hole for external probes.

Technology and Functionality

- Dynamic cooling system for even temperature distribution.
- Automatic defrost to minimize maintenance.
- Interior LED lighting, automatically activated when the door is opened or via manual switch.
- Compatible with clean Hydrocarbon gases, environmentally friendly.
- Climate class 4, designed to operate in conditions up to 32 °C and 60% humidity.

Control and Safety

- Visual and audible alarms for out-of-range temperatures, open door, or sensor errors.
- Safety thermostat to prevent drops below 2 °C.
- Technological compatibility with RS 485 and volt-free contact.
- Display with XL letter size for easy reading.

Efficiency and Sustainability

- Acoustic emissions <50 dB, for quiet operation.
- Energy rating B or A, optimizing electrical consumption.

Available Options

- Voltage: 110/60 Hz and 220/60 Hz.
- INOX shelves and INOX exterior finish.
- Pedal door opening for greater convenience.
- USB for data download as an alternative to WiFi.







Packaging dimensions: Gross length (Front view): 730 MM Gross width (Depth): 880 MM Gross height 2185 MM Gross / packaged weight: 160 KG

MEASURES AND WEIGHT		
Net High (mm):	2037	
Net Depth (mm):	860	
Net Width (mm):	695	
Gross weight / packaged (kg):	160	
Gross height / packaged (mm):	2185	
Gross width / packaged (mm):	880	
Gross length / packaged (mm):	730	
PRODUCT SPECIFICATIONS MEDICAL		
Wheels:	Yes	
Lock:	Yes	
Inner material:	Stainless steel	
Number of bodies:	1	
Plug type:	European (Type F)	
Phases:	1N	
Noise level (dB):	58	
Market Scope:	European	
Gross internal volume (L):	545	
Shelf material:	Plastic-coated Steel	
Reversible door L/R:	Yes	
Ozone:	No	
Number of shelves:	5	
Inner height (mm):	1392	
Inner width (mm):	533	
Inner depth (mm):	683	
External material:	Pre-lacquered sheet metal	
Insulation thickness:	80	
External probe access (number):	1	
Sliding pull-out drawers:	No	
COLD TECHNICAL SPECIFICATIONS MEDICAL		
Gas type:	R-290	
Refrigeration power (KW):	0.535	
Condensation system:	Vent.	
Lamp (W):	6	
Termperature:	-26 -10 °C	
SubFamilia:	CO2	
Team:	Airtight	
Cooling gas load (KG):	0,400	
GWP:	3	
Numero compartimientos:	Uno	
Type of cooling:	Ventilated	
Number of compressors:	1	
ELECTRICITY TECHNICAL SPECIFIC. M	FDICAL	
Electric frequency:	50Hz	
Electric power (KW):	0,471	
Voltage:	230V	
Amperage (A):	4,95 A	
Amperage (A).	T,30 A	

CONTROLLER SECURITY MEDICAL		
High-low temperature alarm:	Yes	
Power failure alarm:	No	
Low battery alarm:	No	
Probe failure alarm:	Yes	
Door open alarm:	Yes	
Battery back-up 72h:	No	
USB port:	No	
RS485:	Yes	
Max and min temperature memory:	Yes	
Power free contact:	Yes	
Safety thermostat:	No	
Data Logger:	No	
WIFI connection:	No	
Controller with password:	Yes	
Touch screen:	Yes	
ENERGY EFFICIENCY LABEL EURO MEDICAL		
Climate class:	4	
Clasif. Energy efficiency:	D	
Power consumption 24h (KWH):	7,540	



Related families



EVO Line