

The VT low temperature freezers creates the possibility to maintain temperatures as low as  $^{-}45^{\circ}\text{C}$ . Supreme stability, reliability, user-friendliness and ease of cleaning make these freezers an ideal solution for laboratories and hospitals.



Outor Dimonsions HyWyD mm	005/1065/005	
Outer Dimensions HxWxD, mm  Inner Dimensions HxWxD, mm	885x1265x605 635x1100x440	
Weight Gross/Net, kg	73,2 / 67,	
Material inner cabinet	Painted Stee	
Material outer cabinet	Painted Stee	
Packaging weight, kg	ruinteu ster	
Packaging dimensions HxWxD, mm	900x1313x72	
Insulation thickness, mm	8	
Insulation type	Polyurethane with Cyclopentane	
Mobility / Castors	Ye:	
Refrigerant, Type	R290	
Number of compressors		
Internal Air Distribution	Stati	
Number of Probes		
CONTROLLER		
Controller	XR30C	
Controller language	No language - only 3 digi	
USB Connection	N	
Logging	٨	
Temperature Graph	1	
High/Low Temp. Alarm	Ye	
Open Door Alarm	N	
Probe Failure Alarm	Ye	
Power Failure Alarm	No	
STORAGE		
Volume, Gross/net, L	29	
Baskets		
Basket material	Steel coated with plastic powde	
Inner lids	N	
FEATURES		
Lock	Ye	
LED Light	No	
Battery Backup for Controller, 24h	No	
Porthole	Yes - Ø 12 mn	
Dry Contact	No	
Door	Solie	
Door Reversibility	N/ <i>i</i>	



BIOMEDICAL

The VT low temperature freezers creates the possibility to maintain temperatures as low as  $^{-}45^{\circ}\text{C}$ . Supreme stability, reliability, user-friendliness and ease of cleaning make these freezers an ideal solution for laboratories and hospitals.

Frequency	Hz	50H.
Max Ambient	°C	30°0
Max Humidity	% rh	559
PERFORMANCE		
All data in RT20°C		
Temperature Range	°C	-10 to -45
Uniformity in performance - difference +/- from Avg set point	°C	
Pull down time (from 25 to factory setpoint)	Minutes	100
Hold over time (from factory SP to -25, -40 and -60) Empty	Minutes	
Refrigerant		R290
Number of probes	pcs	
Defrost	y/n	No
Internal air distribution		Static
Number of compressors	pcs	
Safety thermostat	y/n	No
Energy 24 hours, in 25°C	kWh/24h	3,74
Energy year, in 25°C	kWh/year	1365

2