




Type	Upright
Volume total	711 litre
Usable volume 2/4 compartments	663/654 litre
Storage capacity 2"boxes/50 mm	528
External dimensions	1195/1140 x 888 x 1992 mm
Internal dimensions	890 x 626,5/592 x 1276 mm
Compartments/inner doors/platforms	4/2/3 in height adjustable
Main door	With lock and keys
Inner doors	Stainless steel, insulated
Material internal/external	Stainless Steel/Epoxy Coated steel
Placed on	Heavy duty castors, in front with brakes
Insulation	Polyurethane
Cooling	Two (2) cascade connected compressors
Refrigerants	First stage: R455A/Second stage: R170
Condenser	Air-cooled
Temperature adjustments	-50°C till -86°C (other range; on request)
Controller	Web-based microprocessor
Display	7" Touchscreen in main door at eye level
Temperature history	On display with scroll function
Data storage	At least 12 months
Temperature sensors	PT1000
Backup battery	Alarming and monitoring during power failure
Alarming	Optical and acoustic, but also possible via E-Mail
Communication	Telephone dialling activation system Potential (Voltage) free contact RJ45 (Ethernet) connection USB connection
Software	I-freeze
CO ₂ -backup system	Partially prepared
Transit/vacuum release	Ø 26 mm/vacuum release situated in transit
Cable entry ports	Two (2)
Compressor room	Well-arranged layout and very easy filter exchange
Requirements	220/240 VAC, 50 Hz, fuse 16 Amp. slow
Power and current rating	1230 VA/1125 W/5,3 Amp.
Energy consumption	13,5 kWh/24h
Heat exchange	0,53 kW/h
Noise level	54 dBA
Net weight	375 kg
CE certified	EN61010-1:2010, EN60601-1-2:2007

OPTIONS

Hybride Cooling System
Water cooling
CO ₂ -backup system
LN ₂ -backup system
Extended backup system
Temperature chart recorder
Voltage stabilizer
Transformer
IQ/OQ/PQ
Electronic lock main door
Padlock on main door
Left hinged door(s)
3, 4, 5 or 6 compartments/inner doors
Inner doors lockable by key
Levelling feet
Alarming by texting and/or phone
Sliding shelves with hinged front
Drawers in Aluminium or Stainless Steel
Racking systems in Aluminum or Stainless Steel
Cryo Boxes
Cryo Gloves



DRAWER RACKING SYSTEM*1

Model #	Comp.	# Racks	# Boxes per rack	Total boxes 133x133	Total plates 128x85	Max. height box
DSA-7336-136G	4	24	42		1008/1176*2	33 mm
DSA-5504-136G	4	12	20	528*2	792/924*2	50 mm
DSA-6504-136G	4	12	24			
DSA-11524-136G	2	12	44	528	792/924*2	52 mm
DSA-D211524-136G	2	6	88	528	792/924*2	52 mm
DSA-5534-136G	4	24	20	480	720/840*2	53 mm
DSA-7844-136G	2	12	28	336		84 mm
DSA-D27844-136G	2	6	56	336		84 mm
DSA-3914-136G	4	24	12	288		91 mm
DSA-21284-136G	4	24	8	192		128 mm

*1 other dimensions on request. *2 only on request.

SIDE ACCESS RACKS

Model #	Comp.	# Racks	# Boxes per rack	Total boxes 133x133	Maximum height box
HR-4-6-45	4	24	24	576	45 mm
HR-4-5-53	4	24	20	480	53 mm
HR-4-3-76	4	24	12	288	76 mm
HR-5-FLEX	4	24	20/12	480/288	55/95 mm

Laurent Janssensstraat 105
5048 AR Tilburg
The Netherlands
T +31 13 750 15 55
F +31 13 463 86 35
info@snijderslabs.com
www.snijderslabs.com