



Emerald Class

Leading Naturally













Key Features

The FM-8oKE-HC/HCN are self-contained ice makers, which utilise Natural Refrigerant R290.



- Energy efficient, with savings of 10% compared to HFC equivalent model.*
- Member of the Emerald Class, Hoshizaki's range of climate friendly ice makers.
- Can produce up to 85 kg of ice (flake) and 75 kg (nugget) per 24 hours (AT.10°C.WT.10°C).
- Automatic flush system to reduce sediment build up.
- Closed water circuit offers the ultimate contamination protection, by reducing the number of points at which impurities can enter the ice making process.
- Electronically controlled to ensure an optimised ice making process under varying circumstances without the need for physical adjustments. Quality of ice is always consistent.
- Easily cleanable air filter allows end-users to carry out routine cleaning schedules. Extends product life expectancy and reduces the frequency and costs of maintenance call-outs.
- Stainless steel exterior with integrated door handles provides a hygienic and high quality finish.
- Based on Internal comparative study. Please contact your local sales branch to find out more.





Available Models

Model	Air Cooled	Water Cooled
FM-8oKE-HC	~	
FM-8oKE-HCN	~	

Bins

Model	Type of Bin	Max. Bin Capacity approx.
FM-8oKE-HC	Self-contained	26kg
FM-8oKE-HCN	Self-contained	32kg

Production

without prior notice.

Model	Ice Production per 24h approx.	Temperature	Water Consumption per 24h approx.
FM-8oKE-HC	Approx. 85kg	AT 10°C, WT 10°C	0,085m³
	Approx. 75kg	AT 21°C, WT 15°C	0,075m³
	Approx. 60kg	AT 32°C, WT 21°C	0,060m³
FM-8oKE-HCN	Approx. 75kg	AT 10°C, WT 10°C	0,075m³
	Approx. 65kg	AT 21°C, WT 15°C	0,065m³
	Approx. 50kg	AT 32°C, WT 21°C	0,050m³











FM-8oKE-HC/HCN FLAKE/NUGGET ICE MAKER


Leading Naturally


FM-8oKE-HC/HCN


OCAD drawings available on our website

AIR AIR AIR AIR AIR

D15998 / 2015.04.24







Specifications

	FM-8oKE-HC/HCN
Dimensions W x D x H (mm)	640 x 600 x 800 (Legs 89mm)
AC Supply Voltage	1/220 - 240V/50Hz
Electrical Capacity (kW)	0,270
Heat Rejection (AT 32°C, WT 21°C)	450W
Refrigerant Charge	R290
Weight Gross / Net	75kg / 65kg

Operation Requirements

Ambient Temperature	5 - 40°C	
Water Supply Temperature	5 - 35°C	
Water Supply Pressure	0,5-8bar (0,05-0.8MPa)	
Voltage Range	Rated Voltage ± 6%	

Accessories

Scoop	
Installation Kit	



Hoshizaki Export

Keienbergweg 50 C/D 1101 GC Amsterdam The Netherlands

T: +31 (0)20 6918499 F: +31 (0)20 6918768 www.hoshizaki-europe.com www.gram-commercial.com